



Krytox™
Performance Lubricants

Greases for Corrugators

Product Information

Krytox™ PFPE/PTFE greases have become the corrugator industry standard for lubricating bearings on heated rolls in single facers and associated equipment. Krytox™ lubricants help eliminate bearing lubrication as a cause of premature corrugator roll failure. Corrugator roll changes are significantly easier and quicker on single facers lubricated with Krytox™ greases.

Corrugators choose Krytox™ lubricants for many reasons:

- Most productive lubrication system for single facer bearings among all paper corrugating plants, equipment OEMs, and corrugator roll rebuilders
- Most thermally stable H-1 base oil available
- Reduced risk of bearing failure
- Conversion support and PFPE lubrication/application training available

Krytox™ greases for the corrugating industry include:

Krytox™ Corrugator (CORR) 226FG, 227FG Greases—
The standard in PFPE/PTFE greases, recognized by OEMs and operators alike as the premium performing high temperature grease. These products are NSF H-1 food grade registered, providing safe, non-toxic, and inert performance in food-related operations.

Safe Handling

For detailed information, refer to the SDS for the specific grade of Krytox™ fluorinated grease that you are using. Highlights are:

- When handling, wear any type of impervious rubber gloves.
- Wash hands after use.
- Do not smoke tobacco that may have been contaminated with Krytox™ grease. Inhalation of fumes from burning




Krytox™ grease may cause a temporary flu-like illness with symptoms such as fever, chills, and sometimes cough. Symptoms are typically gone after 1-2 days.

- When handling Krytox™ solvent or HC cleaner, use adequate ventilation, and wear eye protection and any type of impervious rubber gloves.

Key Points

- Make sure the bearings are clean and free of preservatives, hydrocarbon oils, greases, and residues before lubricating with Krytox™ grease; use Krytox™ HC Plus Cleaner or equivalent. *Contaminating Krytox™ grease with any other lubricant will impair its lubricating value.*
- If using pails versus cartridges, slight pooling of oil on top of the Krytox™ grease can occur, particularly if it has been sitting unused for a while. Simply mix it back in with a clean stirrer.
- Use special grease fittings—pin or button head—for Krytox™ grease to prevent contamination with hydrocarbon or synthetic lubricants.



- Use a dedicated grease gun (labeled Krytox™ grease only) with a swivel coupling matched to the special pin or button head grease fittings (bearing inlet ports). Fill the bearings and bearing housings completely to prevent air pockets that can collect water and debris.
- Prevent corrugating process materials (e.g., waxes and paper debris) from entering the bearings.

Relubrication

- Wipe the inlet fittings clean with a clean cloth to prevent contamination of the Krytox™ grease.
- Add/replenish Krytox™ grease every three months. Pump about 1 lb (1/2 cartridge), or whatever is necessary, of Krytox™ grease into the bearing pin or button head grease fittings to force some existing grease out through the seals. It is best to rotate bearings while adding grease to prevent “channeling” of the new grease through the bearing. A more conservative approach is to follow this practice

more frequently, say once a month; proportionately less Krytox™ grease would be needed. **Pay attention to plant safety procedures when working with moving equipment.**

- Compare expelled/purged grease with the “Color Guide” and service as noted. (This guide applies to normal wear only; contaminants will alter the grease’s appearance.)
- Wipe off excess Krytox™ grease from equipment surfaces to prevent buildup of dirt/debris attracted to surface grease.

Disposal and Storage

- Properly dispose of used Krytox™ grease purged from outlet ports, seals, and/or shaft-bearing clearances according to local, state, and federal codes.
- Keep all Krytox™ grease containers **covered** to prevent contamination.

Color Guide

Color	Contamination	Recommendation
White	None	Grease in good condition; creamy consistency
Gray	0.0–0.1% iron	Grease in good condition; normal wear in bearing; creamy consistency
Tan	0.1–0.4% iron	Add grease until cavity is full; bearing okay
Brown	0.4–0.8% iron	Flush bearing with grease until color lightens to tan.
Dark Brown	Greater than 0.8% iron	Check bearing for play and noise. If okay, flush/purge with new Krytox™ grease. If not okay, schedule bearing change.
Black		Replace bearing.

The information set forth herein is furnished free of charge and based on technical data that Chemours believes to be reliable. It is intended for use by persons having technical skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Because conditions of product use are outside our control, Chemours makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. As with any material, evaluation of any compound under end-use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

NO PART OF THIS MATERIAL MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR BY ANY MEANS ELECTRONIC, MECHANICAL, PHOTOCOPYING, RECORDING OR OTHERWISE WITHOUT THE PRIOR WRITTEN PERMISSION OF CHEMOURS.

For product information, industry applications, technical assistance, or global distributor contacts, visit krytox.com or within the U.S. and Canada, call 1-844-773-CHEM/2436 or outside of the U.S., call 1-302-773-1000.

© 2019 The Chemours Company FC, LLC. Krytox™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC. Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Replaces: H-89959-3
C-10273 (1/19)