



Krytox™ AUT 2E68

Performance Lubricants

Grease for Automotive Applications

Product Information

Krytox™ AUT 2E68 grease was developed to address the automotive industry's need for lubricants that combine efficiency and performance at both high and low temperatures. These include such usages as viscous fan clutch bearings, alternators, throttle bodies, and other demanding applications. Krytox™ AUT 2E68 grease has exceptionally low start-up performance, but still provides low volatility, as well as outstanding thermal, oxidative, and corrosion resistance.

Krytox™ oils and greases are based on perfluoropolyether oils and can be utilized in extreme conditions and environments.

These include both continuous high temperatures up to 300 °C (572 °F) and even higher temperatures for shorter periods of time, depending on product grade limits. They are nonflammable and safe for use in oxygen service. They are chemically inert and safely used around hazardous chemicals. They do not damage plastics or elastomers nor cause corrosion to metals. They are commonly used as lubricants in aerospace, automotive, industrial, and semiconductor applications, as well as solving many other routine lubrication problems.

Typical Properties*	Krytox™ AUT 2E68 Grease
Base Oil Viscosity, cSt, ASTM D445	
-40 °C (-40 °F)	5215
40 °C (104 °F)	72.6
100 °C (212 °F)	18.92
Useful Temperature Range, °C (°F)	-55 to 180 (-67 to 356)
Oil Pour Point, °C (°F), ASTM D97	-60 (-76)
Oil Volatility, % in 22 hr (D2595), 204 °C (400 °F)	3.0
Oil Separation, % at 150 °C (302 °F), ASTM D6184	6
Standard NLGI Grade	1.5
Density, g/mL, ASTM D4052	1.87

*These values are typical properties and not product specifications.

The information set forth herein is furnished free of charge and based on technical data that Chemours believes to be reliable. It is intended for use by persons having technical skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Because conditions of product use are outside our control, Chemours makes no warranties, express or implied, and assumes no liability in connection with any use of this information. As with any material, evaluation of any compound under end-use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

NO PART OF THIS MATERIAL MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR BY ANY MEANS ELECTRONIC, MECHANICAL, PHOTOCOPYING, RECORDING OR OTHERWISE WITHOUT THE PRIOR WRITTEN PERMISSION OF CHEMOURS.

For product information, industry applications, technical assistance, or global distributor contacts, visit krytox.com or within the U.S. and Canada, call 1-844-773-CHEM/2436 or outside of the U.S., call 1-302-773-1000.

© 2023 The Chemours Company FC, LLC. Krytox™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC. Chemours™ and the Chemours Logo are trademarks of The Chemours Company.